


1. The Attachacam Camera Mount

- A. Black Lever Handle | B. Mounting Attachment
- C. Connecting Screw | D. Camera Mount
- E. (1/4 20 UNC) Thumbscrew
- F. Fine Adjustment Screw: For fine tilt adjust




NO TOOLS NEEDED!

2. Assembling Attachacam to Standard Position (Mounting from above)

- Tighten black lever handle (A.) to connect mount (B.)
- Slightly loosen fine adjustment screws (E.)
- Pair the connecting camera mount piece (D.) to attaching mount (B.) with connecting screw (C.)
- Place still or video camera on camera mount (D.) with use of thumbscrew (E.)


To attach mount to tube/barrel:

- Loosen black lever handle (A.) and position mount (B.) on barrel/tube
- Securely tighten black lever handle (A.) until mount (B.) is fastened securely'




3. Reverse Mounting: From Standard Position (Mounting from below)

- Invert attaching mount (B.)
- Slightly loosen fine adjustment screws (E.)
- Pair the connecting camera mount piece (D.) to attaching mount (B.) with connecting screw (C.)
- Place still or video camera on camera mount (D.) with use of thumbscrew (E.)
- Screw still or video camera on camera mount (D.) by tightening thumbscrew (E.)
- Place mount (B.) around barrel/tube and securely tighten black lever screw (E.)
- Tighten fine adjustment screws (E.) to "zero-in" on sights as needed




4. Overhead Mounting: From Standard Position

- Invert and turn camera mount (D.)
- Mount will be above and along the left side of mount (B.)
- Slightly loosen fine adjustment screws (E)
- With use of screwdriver, securely screw connecting camera mount (D.) to attaching mount (B.) with connecting screw (C.)
- Unscrew thumbscrew (E.) and invert thumbscrew (E.)
- Place still or video camera on camera mount (D.) with use of thumbscrew (E.)
- Screw still or video camera on camera mount (D.) by tightening thumbscrew(E)
- Place mount (B.) around barrel/tube & securely tighten black lever screw (E.)
- Tighten fine adjustment screws (E) to "zero-in" on sights as needed



5. Mounting Below Barrel: From Standard Position (Side mount)

- Invert attaching mount (B.)
- Slightly loosen fine adjustment screws (E)
- Using screwdriver, securely screw connecting camera mount piece (D.) to attaching mount (B.) with connecting screw (C.)
- Place still or video camera on camera mount (D.) with use of thumbscrew (E.)
- Screw still or video camera on camera mount (D.) by tightening thumbscrew (E.)
- Place mount (B.) around barrel/tube and securely tighten black lever screw (E.)
- Tighten fine adjustment screws (E) to "zero-in" on sights as needed



6. Bow Mount

- Unscrew Connecting screw (C.)
- Remove fine adjustment screws (F)
- Turn mount (B.) 180°
- Place still or video camera on camera mount (D.) with use of thumbscrew (E.)
- Screw still or video camera on camera mount (D.) by tightening thumbscrew (E.)
- Place mount (B.) around stabilizer and securely tighten black lever screw (E.)
- Screw connecting screw (C.)
- Place still or video camera on camera mount (D.) with use of thumbscrew (E.)
- Screw still or video camera on camera mount (D.) by tightening thumbscrew (E.)
- Place mount (B.) front of bow and securely tighten black lever screw (A.)

